

CA 6 1 5 K



HEAT-RESISTANT LEATHER HIDE WELDER'S GLOVE / KEVLAR® SEWN

Ref. CA615K



Product specifications

High quality heat-resistant split leather (HR). Cuff with canvas lining. Kevlar® Technology sewn. American assembly. Length: 35 cm.

Upper split leather cowhide heat-resistant treated.

Thickness between 1.2 and 1.4 mm.

Hand lining: batting.

Cuff lining: cotton fabric weight of 300 g/m².

Kevlar® Technology sewn.

COLOUR

Red

SIZE

10

Product Use - Risks



Heat



Wearing



Heavy industry

Certifications and Standards



PPE DIRECTIVE EC 89/686

EN420:2003 General requirements

EN388:2003 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 3: Resistance to abrasion (from 1 to 4)
- 1: Resistance to cutting (from 1 to 5)
- 3: Resistance to tear (from 1 to 4)
- 3: Resistance to puncture (1 to 4)

EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)




- 4: Resistance to flammability (from 1 to 4)
- 1: Resistance to contact heat (from 1 to 4)
- 3: Resistance to convective heat (from 1 to 4)
- X: Resistance to radiant heat (from 1 to 4)
- 4: Resistance to small projections of liquid metal (from 1 to 4)
- X: Resistance to large projections of molten metal (from 1 to 4)

EN12477:2001/A1:2005 Protective gloves for welders

TYPE A: Welding - Other welding processes - less dexterity - Type A

References

References	Bar code	COLOUR	SIZE		
CA615K10	3295249021597	Red	10	60	12