




ANTI STATIC
100 K Ω - 1000 M Ω

LF-02

S.NO.	NAME	SPECIFICATION
1	Opreative Standard	IS 15298 (Part-2): 2016 & EN-20345:2011
2	Design Type	Slip on, low ankle
3	Sizes Available	3 to 8 37 to 42
4	Weight Chart	Size 3: 615 gms, 4: 625 gms, 5: 645 gms, 6: 665 gms, 7: 685gms, 8: 705 gms * Tolerance $\pm 2\%$
5	Shoe Upper Components	<ul style="list-style-type: none"> * Genuine grain leather 1.80 mm - 2.00 mm thick & tested for chromium VI content absence * Vamp lining - high tenacity polyester fibre, characterised by high abrasion resistant * Quarter lining - high abrasion-resistant nylon fabric laminated with high-density PU foam for cushioning comfort * Thread - Nylon thread is being used which has high elongation and tensile properties
6	Insocks	High abrasion nylon fabric laminated with Neoprene EVA for a better rebound while walking with antistatic properties
7	Sole	Monodensity sole made by hybrid polyurethane material with antistatic properties giving it robust shelf life, suitably designed for slip and abrasion resistance
8	Toe Cap	The steel toe cap is EN-12568:2010 marked. It is high carbon steel and powder coated for desired impact and compression strength and maintains anti-corrosive properties
9	Application	Mild chemical industry, construction industry, automobile industry, hospitality & facility management
10	Approval	<p>IS : 15298 : PART 2</p>  <p>CM/L-9954209</p>