




100%
METAL
FREE



ANTI STATIC
100 KΩ- 1000 MΩ

MF 01

S.NO.	NAME	SPECIFICATION
1	Opreative Standard	IS 15298 (Part-2): 2016 & EN-20345:2011
2	Design Type	Low ankle
3	Sizes Available	6 to 11 or 40 to 45
4	Weight Chart	Size 6: 805 gms, 7: 815 gms, 8: 830 gms, 9: 870 gms, 10: 890 gms 11: 930 gms * Tolerance $\pm 2\%$
5	Shoe Upper Components	<ul style="list-style-type: none"> * Genuine grain leather 1.80 mm - 2.00 mm thick & tested for chromium VI content absence. Apollo print. * Vamp lining - high tenacity polyester fibre, characterised by high abrasion resistant * Quarter lining - high abrasion-resistant airmesh fabric laminated with high-density PU foam for cushioning comfort * Thread - Nylon thread is being used which has high elongation and tensile properties * EYELETS - PLASTIC COMPOSITE
6	Insocks	MEMORY COMFORT INSOCKS: It is PU Insock that forms contours according to the shape of the feet that helps in nice distribution of body weight across the feet. The foam gives a permanent sense of comfort upon stepping and reduces the fatigue considerably
7	Sole	Monodensity sole made by hybrid polyurethane material with antistatic properties giving it robust shelf life, suitably designed for slip and abrasion resistance
8	Toe Cap	COMPOSITE TOE CAP is EN-12568:2010 marked. 40% lighter in weight than steel toe cap, non-magnetic
9	Application	Mild chemical industry, construction industry, automobile industry, hospitality & facility management, Electronic industry
10	Approval	<p>IS : 15298 - PART 2</p>  <p>CM/L-9954209</p>