




ANTI STATIC
100 KΩ- 1000 MΩ

SOCCER

S.NO.	NAME	SPECIFICATION
1	Operative Standard	IS 15298 (Part-2): 2016 & EN-20345:2011
2	Design Type	Low ankle
3	Sizes Available	5 to 11 or 39 to 45
4	Weight Chart	Size 5: 940 gms, 6: 960 gms, 7: 980 gms, 8: 1010 gms, 9: 1060 gms, 10: 1110 gms 11: 1130 gms * Tolerance $\pm 2\%$
5	Shoe Upper Components	<ul style="list-style-type: none"> * Genuine grain leather 1.80 mm - 2.00 mm thick & tested for chromium VI content absence * Vamp lining - high tenacity polyester fibre, characterised by high abrasion resistant * Quarter lining - high abrasion-resistant nylon fabric laminated with high-density PU foam for cushioning comfort * Thread - Nylon thread is being used which has high elongation and tensile properties * D-Eyelets - powder coated anti-rust
6	Insocks	ORTHO BOUNCE INSOCKS <ul style="list-style-type: none"> * Retains same thickness & hence same shoe fitting throughout service life * Breathable open cell material keeping feet dry & comfortable * Pro-anti fatigue technology absorbs shocks with every step with high energy return * Pro-high rebound cushion insole
7	Sole	Dual density sole made by hybrid polyurethane material with antistatic properties giving it robust shelf life. Low density mid sole enhances cushion and flexibility and high density outsole enhances abrasion and tear resistance.
8	Toe Cap	The steel toe cap is EN-12568:2010 marked. It is high carbon steel and powder coated for desired impact and compression strength and maintains anti-corrosive properties
9	Application	Mild chemical industry, construction industry, automobile & engineering industry, hospitality & facility management
10	Approval	IS : 15298 : PART 2  CM/L-9954209