



Hand protection

FBN49

WORKS IN DRY ENVIRONMENT

Mechanical leather glove, the American cut prevents the seams from being uncomfortable on the underside of the hand



Applications

- Public works
- Building
- Finishing works / Craftsmanship
- Maintenance
- Automotive
- Temporary work

Certifications and norms



Protects against risks



Wearing



Hand protection

FBN49

WORKS IN DRY ENVIRONMENT

Mechanical leather glove, the American cut prevents the seams from being uncomfortable on the underside of the hand

Standards - Details



EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
2 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997

Technical details

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical glove kind	Cut and sewn
Thickness	0,9 -> 1,1 mm
Cuff characteristic	Sewn open cuff with elastic
Benefits element	Vendor pack
Color	Natural
Size	7, 8, 9, 10, 11
Type of packaging	Pack of 12



Safety gloves

FBN49

WORKS IN DRY ENVIRONMENT

Mechanical leather glove, the American cut prevents the seams from being uncomfortable on the underside of the hand

Logistics information

Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight
-----------	--------	------	-------------	-------	----------	----------------	---------------	--------